






Gauges and Other Accessories

COALESCENT & FILTER DIFFERENTIAL GAUGE KITS

A differential gauge measures pressure drop across the element indicating a replacement element is needed when the drop increases into the range of 7-10psi (0.5 - 0.7 bar). Gauges can be ordered with product or, if product is equipped with gauge ports, as kits. Availability noted on individual product pages.

Product Model	Type	Part Number	
GUARDSMAN	Small Slide, short screws	A60F-28	
Series 350	Small Slide, long screws	A125-09	
VANGUARD, Series 380	Small Slide, plastic bolts	103-151	
VANGUARD, Series 380	Large dual face	106-35	
VANGUARD, Series 380	Large dual face, Reed switch normally open	106-35E	
VANGUARD, Series 380	Large dual face, Reed switch normally closed	106-35EC	

LUBRICATOR QUICK FILL CAP

Quick-Fill Caps (Q-Caps) are check valve fittings. They can be ordered as a lubricator option or separately as kits. Kits include Q-Cap assembly and o-ring.



Product Model	Part Number
Miniature, Sentry & Guardsman	A203-8BH
Vanguard	A204-8BH
Series 350	KA126-09
Series 380	KA117-109

LUBRICATOR QUICK FILL HOSE COUPLER

The Quick Fill Hose Coupler is used on the end of an oil fill hose assembly to attach to a Quick Fill Cap which has been installed on a lubricator. This allows for easier oil refills.



Quick Fill Hose Coupler	Part Number
1/8" NPTF Female	A10001

REGULATOR PRESSURE GAUGES

Gauges are back mounted, with shatterproof plastic faces for use in rugged environments. Large numerals display psig in red and bar in black. Heavy duty construction of bourdon and indicator dial. Accuracy within 2 to 3 percent. Refer to specifications on regulator product pages for appropriate gauge port size.



Sentry and Miniature Gauges

Range psig (bar)	Dial Diameter Inch (mm)	Gauge Port Size NPTF	Part Number
0-30 (0-2.1)	1.5 (38)	1/8"	30MDD*
0-60 (0-4.1)	1.5 (38)	1/8"	60MDD*
0-160 (0-11)	1.5 (38)	1/8"	70MDD*

* Add "W" to end of number for BSPT.

Guardsman, Vanguard, 350 & 380 Gauges

Range psig (bar)	Dial Diameter Inch (mm)	Gauge Port Size NPTF	Part Number
0-30 (0-2.1)	2 (51)	1/4"	30BDD
0-60 (0-4.1)	2 (51)	1/4"	60BDD*
0-200 (0-13.8)	2 (51)	1/4"	200-BDD*
0-300 (0-20.7)	2 (51)	1/4"	300-BDD*
0-600 (0-41.4)	2 (51)	1/4"	600-BDD*

* Add "W" to end of number for BSPT.

Gauge Kits for HPR100 & HPR180

Kits include adaptor/reducer bushing and gauge



Range psig (bar)	Dial Diameter Inch (mm)	Gauge Port Size NPTF	Part Number
0-200 (0-13.8)	2 (51)	1/4"	A200-BDD-2*
0-200 (0-13.8)	2 (51)	3/8"	A200-BDD-3*
0-200 (0-13.8)	2 (51)	1/2"	A200-BDD-4*
0-300 (0-20.7)	2 (51)	1/4"	A300-BDD-2*
0-300 (0-20.7)	2 (51)	3/8"	A300-BDD-3*
0-300 (0-20.7)	2 (51)	1/2"	A300-BDD-4*

* Add "W" to end of number for BSPT.

FILTER TUBE-AWAY DRAIN KITS

Tube-Away kits carry liquid drainage to a remote disposal point through 3/16th flexible tubing. Kits are suitable for all general purpose and coalescent filters. Available in three lengths.



Length of Tubing	Part Number
3 ft (1 meter) tubing	K802-21-3
6 ft (2 meter) tubing	K802-21-6
12 ft (4 meter) tubing	K802-21-12