

Mufflers - Silencers


M200 and M201 Models Port Size: 1/8 to 2-1/2




Model Shown: M200-6



Model Shown: M201-16



Male pipe threads
For ports 1/8 through 1-1/4



Female pipe threads
For ports 1-1/4 through 2-1/2

DIMENSIONS

Port Size	NPT Threads	Avg. C _v	A Inches (mm)	B Inches (mm)	Weight lb (kg)
1/8	Male	2.0	0.8 (21)	2.2 (56)	0.3 (0.1)
1/4	Male	2.7	0.8 (21)	2.2 (56)	0.3 (0.1)
3/8	Male	3.2	0.8 (21)	2.2 (56)	0.3 (0.1)
3/8	Male	4.9	1.3 (32)	3.8 (96)	0.5 (0.2)
1/2	Male	5.9	1.3 (32)	3.8 (96)	0.5 (0.2)
3/4	Male	5.9	1.3 (32)	3.8 (96)	0.5 (0.2)
3/4	Male	13.5	2.0 (51)	5.6 (142)	1.5 (0.7)
1	Male	16.7	2.0 (51)	5.6 (142)	1.5 (0.7)
1-1/4	Male	17.4	2.0 (51)	5.6 (142)	1.5 (0.7)
1-1/4	Female	37	2.5 (64)	5.9 (149)	2.3 (1.0)
1-1/2	Female	37	2.5 (64)	5.9 (149)	2.3 (1.0)
2	Female	54	3.0 (77)	7.3 (185)	3.5 (1.6)
2-1/2	Female	65	4.0 (102)	6.9 (173)	3.5 (1.6)

Noise control solutions for air exhaust.

The muffler-silencers substantially reduce exhaust noise levels yet produce little back pressure. Typical impact noise reduction is in the 20-25 dB range.

ORDERING INFORMATION

Change the letters in the sample model number below to specify the Muffler you want.

M20 0-4 W

THREAD and PORT TYPE

- 1/8" C_v: 2.0 Male thread 0-1
- 1/4" C_v: 2.7 Male thread 0-2
- 3/8" C_v: 3.2 Male thread 0-3
- 3/8" C_v: 4.9 Male thread 0M-3
- 1/2" C_v: 5.9 Male thread 0-4
- 3/4" C_v: 5.9 Male thread 0-6
- 3/4" C_v: 13.5 Male thread 0M-6
- 1" C_v: 16.7 Male thread 0-8
- 1-1/4" C_v: 17.4 Male thread 0-10
- 1-1/4" C_v: 37 female thread 1-10
- 1-1/2" C_v: 37 female thread 1-12
- 2" C_v: 54 female thread 1-16
- 2-1/2" C_v: 65 female thread 1-20

PORT TYPE

- NPTF threads Leave blank
- BSP* threads W

* BSPP threads on M201 and BSPT threads on M200 mufflers.