


Replacement Parts & Kits

THANK YOU!

You have just purchased a quality M/P Filenco replacement element or bowl drain from Master Pneumatic.

With care in it's installation and maintenance, you can expect it to have a long and economical service life. Before you go any further, please take a few minutes to look over this information, then save it for future reference and for the useful service information it contains.



KEY	DESCRIPTION	PART NO
1	Moisture Indicator	MI375
2	Moisture Indicator w/piping assembly	MI375-25
3	Cover Assembly (<i>Kit includes cover and screen NO filter discs.</i>)	A25-02
4	Cover Assembly (<i>Kit includes cover, screen AND filter discs.</i>)	A25-02M
5	Filter Replacement discs and gasket (<i>kit does not include element bags</i>).	CD-25E
6	Clay Desiccant replacement element kit (<i>includes Gasket</i>)	CD-25NRE
6	Molecular Sieve replacement element kit (<i>includes Gasket</i>)	MS-25NRE
6	Clay Desiccant with Carbon replacement element kit (<i>includes Gasket</i>)	CDC-25NRE
7	Manual drain (<i>Brass pipe w/ petcock</i>)	MD-25
8	Adaptor Plate	AP-25
9	Manual Drain, polycarbonate bowl, guard and adaptor plate.	PGM-25
10	Auto Drain, polycarbonate bowl, guard and adaptor plate.	PGA-25
11	Manual Drain, metal bowl, and adaptor plate	MSM-25
12	Auto Drain, metal bowl and adaptor plate	MBA-25
13	Manual Drain, polycarbonate bowl and guard	PGM
14	Auto Drain, polycarbonate bowl and guard	PGA
15	Manual Drain, metal bowl	MSM
16	Auto Drain, metal bowl	MBA

Element Replacement Instructions

WARNING—BEFORE SERVICING THE UNIT:

- Shut off air supply.**
- Relieve the pressure from the dryer/filter by manually activating the drain unit on the bottom of the housing.**
- Remove the cover clamp (A).
- Remove the cover (4), top screen, used filter disks, and the middle screen (3).
- Remove the used desiccant bag (B).
- Inspect and clean the inside of the dryer/filter housing.
- Remove the plastic protective bag from the new desiccant bag.
- Insert the new desiccant bag into the dryer/filter body making sure the desiccant bag strap is in an upward position.
- Replace the middle screen (3), the new filter disks (5), and top screen (3).
- Inspect the gasket (C) on the top of the housing for drainage and replace if necessary.
- Install the Cover (4).
- Install the clamp (A). Torque 25 in-lbs.
- Record the date of the desiccant bag change on the yellow label that is supplied in the replacement element kit. Affix the label to your dryer/filter housing.