



6701 18 Mile Rd.  
Sterling Heights, MI 48314  
(877) 240-1005

# Air-Operated Double Diaphragm Pump **Air Filters / Regulators**

Don't allow dirty, wet & contaminated air destroy pump performance. Master Pneumatic's Point of Use filters & regulators were specifically designed with your pump's protection in mind.

*Lockouts and lubricators separately.*



## Superior Protection

Master Pneumatic air filters and regulators provides superior pump protection by removing water and particulate from air lines protecting the pump's main air valve.



## Save Money

Master Pneumatic air components save you money with lower energy costs through reduced energy consumption, less demand on compressors and more pump uptime.



## 7 Year Warranty

Our 7 year warranty on all products is the best in the business.

## Optimize Performance

Master Pneumatic air products optimize pump performance through simple air pressure regulation. The simple adjuster knob allows the operator to perfectly proportion pump air needs to improve efficiency, performance and pump life.

- ❑ **Superior** water removal: Up to 98%
- ❑ **Modular** Inline mounting
- ❑ **Easily adjustable** / tamper-resistant pressure setting knob
- ❑ **Polycarbonate** plastic bowls with shatterguard
- ❑ **Designed to remove** particulate to 5 micron from the airstream to protect downstream equipment

Visit us online at **masterpneumatic.com**

# Technical Specifications

Review the technical specifications of Master Pneumatic's Point of Use filters & regulators which were specifically designed with your pump's protection in mind.

	CFDR56M-2H	CFDR60D-2	CFDR60-3	CFDR100-4	CFDR380-6	FDR180-8
<b>MP PART #</b>						
Air Inlet	1/4"	1/4"	3/8"	1/2"	3/4"	1"
Max Air Flow (SCFM)	20	38	110	180	240	275
Filter (um)	5	5	5	5	5	5
Bowl Material	Poly Bowl	Poly Bowl	Poly Bowl	Poly Bowl	Poly Bowl	Poly Bowl
Bowl Capacity	2.0 oz	4.0 oz	4.0 oz	8.0 oz	9.0 oz	16.0 oz
Max Inlet Pressure	150	150	150	150	150	150
Regulating Pressure Range	0 - 125	0 - 125	0 - 125	0 - 125	0 - 125	0 - 125
Dimensions (IN)	6.5" x 1.6" x 1.6"	7.9" x 2.7" x 2.7"	7.9" x 2.7" x 2.7"	11.6" x 3.5" x 3.5"	13.1" x 3.5" x 3.5"	10" x 10.7" x 4.2"
Weight	.5 lbs	1.4 lbs	1.4 lbs	2.5 lbs	3.7 lbs	5.3 lbs

**Max Flow Rate:** 275 SCFM *For additional size(s) and options, please contact Master Pneumatic.*

**Internal Automatic Drain:** Drainage is automatically discharged

Most models are Integral Filter / Regulators.



## Contact Your Local Distributor to Place an Order



Order online:  
**masterpneumatic.com**



Toll-Free in the United States:  
**(877) 240-1005**



Email us:  
**mp@masterpneumatic.com**



6701 18 Mile Rd. Sterling Heights, MI 48314 | (877) 240-1005

Visit us online at **masterpneumatic.com**